

Trust the Japanese technology

Mitsubishi Electric 2D Cross-Flow Laser Processing Machines



The eX series Mitsubishi laser processing machines are among the most advanced laser cutters in the world. Based on 5th generation three-axial Cross-Flow resonators, they ensure maximum output when working with materials whose dimensions are equal to 1,500 x 3,000 mm and thickness is equal to 0.5 to 28 mm.

The Mitsubishi technology provides new possibilities in laser processing at lower operational costs.

Mitsubishi designs and makes by itself all the key components of the laser system, to include the resonator, the cutting system, and the control system. The manufacturing and the final assembly take place in Japan.





Mitsubishi eX laser processing machines stand for:

- high efficiency
- excellent cut quality
- reliability
- low operating costs
- simple operation

Technical specification

| Design of the machine | Mobile optical system, two exchangeable tables | | |
|--------------------------------------|--|--|--|
| Resonator type | Cross-Flow Mitsubishi | | |
| Available resonator power | 4,500 W, 6,000 W | | |
| Control | M700 Mitsubishi, a 15" touch screen | | |
| Maximum working area | 3,100 x 1,565 mm | | |
| Maximum sheet weight | 930 kg | | |
| Outside dimensions | 10,180 x 3,130 x 2,260 mm | | |
| Weight of the machine | 10,000 kg | | |
| Range of operation in the X/Y/Z axes | 3,100/1,565/150 mm | | |
| Startup time | 3 min | | |
| Simultaneous speed X axis, Y axis | 140m/min | | |
| Maximum work speed | 50m/min | | |
| Positioning accuracy | 0.05/500 mm (X axis, Y axis) | | |
| Positioning repeatability | 0.01 mm (X axis, Y axis) | | |
| Head | PH-XS Mitsubishi, Auto Focus, 5", 7.5", and 10" lenses | | |

Cutting range

| 4,500 W | | 6,000 W | |
|-----------------|-------------|-----------------|---------------------|
| black steel | 0,5 - 28 mm | black steel | 0,5 - 28 mm (32 mm) |
| stainless steel | 0,5 - 25 mm | stainless steel | 0,5 - 28 mm (50 mm) |
| aluminum | 0,5 - 18 mm | aluminum | 0,5 - 20 mm (25 mm) |
| brass, copper | 0,5 - 6 mm | brass, copper | 0,5 - 6 mm |

Caution!

The thickness range and the quality of the cut depend on the quality of the input material and the shape of the element being cut. The optional 5" lens is required for cutting reflective materials, such as brass and copper.