



MT12

MT20

Maximum chuck size

Standard: 165 mm (6")
Option: 210 mm (8")

210 mm (8")

Number of turret stations

15 x 2

15 x 2

Maximum bar workpiece size

dia. 51 mm

dia. 65 mm

Spindle drive motor

Standard: 7.5 kW / 30 min x 2
Option: 11 kW / 30 min x 2

Standard: 15 kW / 30 min x 2
Option: 18.5 kW / 30 min x 2

Spindle speed range

45 rpm - 4,500 rpm
30 rpm - 3,000 rpm
60 rpm - 6,000 rpm
(Only 7.5 kW)

42 rpm - 4,200 rpm

Live tool drive motor

2.7 kW x 2

3.0 kW x 2

Selectable standard tool diameter

16 mm

16 mm

Gross weight with loader

5,600 kg

10,800 kg



	MT25
Maximum chuck size	254 mm (10")
Number of turret stations	15 x 2
Maximum bar workpiece size	dia. 65 mm
Spindle drive motor	Standard: 15 kW / 30 min x 2 Option: 22 kW / 30 min (Only left spindle)
Spindle speed range	25 rpm - 2,500 rpm 35 rpm - 3,500 rpm 40 rpm - 4,000 rpm
Live tool drive motor	4.0 kW x 2
Live tool maximum speed	3,000 rpm
Selectable standard tool diameter	20 mm
Total weight (with tool & loader, without tank)	10,400 kg



MT200

Maximum chuck size	210 mm (8")
Number of turret stations	2 turret : 15(upper) & 12(lower) 3 turret : 15(upper & right) & 12(lower)
Maximum bar workpiece size	Standard: dia. 65 mm Option: dia. 80 mm
Spindle drive motor	15 kW / 30 min x 2
Spindle speed range	50 rpm - 5,000 rpm 40 rpm - 4,000 rpm
Live tool drive motor	4.5 kW, 18.0 Nm / continuous x 2
Live tool speed	14.0 kW / max. (4.8kW / comt.) [Max=4500rpm, Time duty 10 (On:3.0se)]
Live tool maximum speed	4,500 rpm
Selectable standard tool diameter	16 mm
Gross weight with loader	10,800 kg